

2D WIRELESS BARCODE SCANNER

DCcode®

DC7122



NEW ABS DESIGN, COMFORTABLE TO USE



2.4G WIRELESS. UPTO 100M RANGE



STORE UP TO 100,000 BARCODES



32 BITS CPU – SUPER DECODING ABILITY.



TECHNICAL SPECIFICATIONS

Scan Type	Area Imager
Lighting Aimer	CMOS 640 x 480
Storage	100,000 Barcodes
Scanning Speed	500 per second
Scan Angle	Rotation 30° / Incline ±55° / Decline ±60°
Resolution	4 mil
CPU	ARM 32 bit Cortex
Battery	2200 mAh Li-ion
Transmission Range	Indoor max 50 meters Outdoor max 100 meters
Interface	USB + Dongle
Prompt Mode	Buzzer, LED
Decoding Capability	UPC-A, UPC-E, Code128, EAN-13, EAN-8, ISBN, Code 93, UCC/EAN-128, GS1 Code39, Code 39 Full ASCII, Codabar, Interleaved 2 of 5, Databar, MSI, Code11, ISBN, ISSN, China post, etc 2D: QR code, PDF 417, Data Matrix, Aztec, Maxicode etc
Electric Voltage	5V DC
Current Ambient	Work 86mA, Standby 42mA, Starting 130mA
Light Immunity	0-100,000 Lux

Mechanical Parameters

Dimensions	170mm x 92mm x 55mm
Weight	176g

Environmental Parameters

Working Temperature	-0°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Humidity	5% to 95% Relative Humidity, Non Condensing
Drop Test	2m

Warranty

24 Months against any manufacturing defect

APPLICATIONS



RETAIL



LOGISTICS



HOSPITAL



JEWELRY



WAREHOUSE



DCcode®

hello@dcodeinternational.in



www.dcodeinternational.in

DELHI NCR MUMBAI AHMEDABAD SURAT TIRUPUR CHENNAI LUDHIANA PUNE KOLKATA COIMBATORE

